



Paragon Industries, L.P.
2011 South Town East Blvd.
Mesquite, Texas
75149-1122
972-288-7557

www.paragonweb.com
info@paragonweb.com

CS-26

- The top and walls lift out of the way for easy loading.
- Heavy-duty air pistons lighten the top.
- The comfortable lid handle stays cool.
- A woven rope seal mounted on all four sides of the top acts as a gasket and cushions the top.
- Lid elements protected in quartz tubes for a cleaner kiln interior.
- Elements in the top and sides for superior heat distribution.
- Deluxe mercury relay
- Easy-maintenance control panel
- On/off switch and pilot light
- Heavy steel base with mar-proof rubber feet
- Digital 12-key Sentry 2.0 controller



Dimensions & Specifications

Max Temp °F	1700°
Cubic Feet	5.18
Firing Chamber	26" Square x 13 ¼"D
Uncrated Outside Dimensions	36 ¼"W x 42"D x 27 ¾"H
Shipping Wt., Kiln	523 lb.
Shipping Wt., Furniture	60
Shipping Dimensions	43"W x 47"D x 36"H
Doorway Clearance Needed	36 ¼"
Volts	240
Amps	30
Watts	7,200
Circuit: Copper Wire Size	8
Circuit: Fuse	40
NEMA Config.	6-30R