



NOTE: SURFACE OF INSULATED WIRES ONLY MARKED ⊗ TO BE COLORED GREEN WITH OR WITHOUT ONE OR MORE YELLOW STRIPES.
 NOTE: GROUNDING SCREW TO HAVE A GREEN COLORED SLOTTED AND/OR HEXAGONAL HEAD, NO SUBSTITUTES. USE PPN-1250

CAUTION!
 TO PROVIDE CONTINUED PROTECTION AGAINST THE RISK OF ELECTRIC SHOCK CUSTOMER'S POWER SUPPLY MUST BE PROPERLY GROUNDED

WIRING NOTE
 ALL WIRES #14 AWG, TYPE SEW/SF2 MINIMUM UNLESS OTHERWISE NOTED

POWER REQ'TS
 240 VOLTS
 1 PHASE
 60 HERTZ
 45 AMPS
 10800 WATTS
 MAX TEMP 2300°F

| TO RE-ORDER ELEMENTS, SPECIFY | | |
|-------------------------------|-----|----------------|
| DESCRIPTION | QTY | LDC |
| ELS99TBM | 6 | TOP, BOT & MID |

| | | | | |
|----------|--|--|----------------|-----|
| COMMENTS | PARAGON INDUSTRIES 2011 SOUTH TOWN EAST BLVD MESQUITE, TEXAS 75149 | PRODUCT DESCRIPTION | PART NO. | REV |
| | | 10 SIDES, 23.5" DIA X 27" DP 240V, 1PH, 60HZ, 45A, 10800W | S99 | - |
| | | | WIRING DIAGRAM | |