



**CAUTION**  
 TO PROVIDE CONTINUED PROTECTION AGAINST THE RISK OF ELECTRIC SHOCK, CUSTOMER'S POWER SUPPLY MUST BE PROPERLY GROUNDED.

NOTE: GROUNDING SCREW TO HAVE A GREEN COLORED SLOTTED AND/OR HEX HEAD NO SUBSTITUTES. USE #1005

NOTE: THE SURFACE OF THE INSULATED WIRES MARKED (X) TO BE COLORED GREEN, WITH OR WITHOUT ONE OR MORE YELLOW STRIPES.

**POWER REQ'TS**  
 240 VOLTS  
 1 PHASE  
 60 HERTZ  
 45 AMPS  
 10800 WATTS  
 2150 °F MAX TEMP

TO RE-ORDER ELEMENTS, SPECIFY

DESCRIPTION	QTY	LOC
ELSNF283TB	6	TOP&BOT
ELSNF283M	6	MIDDLE

LT3K  
 240V 60HZ  
 KILN SITTER  
 W/LIM. TIMER  
 & 4" TUBE  
 ASSY KS7

CR6  
 6-2/8-1 CORDSET  
 6-50P CAP

UL/CUL LISTED

COMMENTS	PARAGON INDUSTRIES 2011 SOUTH TOWN EAST BLVD MESQUITE, TEXAS 75149	<b>PRODUCT DESCRIPTION</b> 12 SIDES 28" DIA X 29" DP 240V 1PH 60HZ 10800W		PART NO SNF283	REV -
		<b>WIRING DIAGRAM</b>			