

CR6  
6-2/8-1 CORDSET  
6-50P CAP

**CAUTION**


TO PROVIDE CONTINUED PROTECTION AGAINST THE RISK OF ELECTRIC SHOCK, CUSTOMER'S POWER SUPPLY MUST BE PROPERLY GROUNDED.

NOTE: GROUNDING SCREW TO HAVE A GREEN COLORED SLOTTED AND/OR HEX HEAD NO SUBSTITUTES. USE #1005

NOTE: THE SURFACE OF THE INSULATED WIRES MARKED (X) TO BE COLORED GREEN, WITH OR WITHOUT ONE OR MORE YELLOW STRIPES.

**POWER REQ'TS**

240 VOLTS  
1 PHASE  
60 HERTZ  
30 AMPS  
7200 WATTS  
MAX TEMP 2000°F




16 OHMS




16 OHMS


TF3  
30A RELAY  
W/12V  
DC COIL




TF3  
30A RELAY  
W/12V  
DC COIL



TF6  
DOOR OPER'D  
POWER CUTOFF  
SWITCH




PY50  
TYPE K T/C




**WIRE SIZES**

NOTE: ALL WIRES TO BE TYPE SEW/SF2, #14 AWG MINIMUM UNLESS NOTED

TF2  
CONTROL  
TRANSFORMER  
OUTPUT=24VAC



TF22  
DTC 1020



1/2 AMP FUSE

| TO RE-ORDER ELEMENTS, SPECIFY |     |      |
|-------------------------------|-----|------|
| DESCRIPTION                   | QTY | LDC  |
| ELHT22                        | 2   | SIDE |
|                               |     |      |
|                               |     |      |

COMMENTS

PARAGON INDUSTRIES  
2011 SOUTH TOWN EAST BLVD  
MESQUITE, TEXAS 75149

**PRODUCT DESCRIPTION**  
21"W, 13.25"H, 21"DP  
240V, 1PH, 60HZ, 30A, 7200W

**PART NO.** HT22D  
**WIRING DIAGRAM**

**REV**  
-