



CAUTION
 TO PROVIDE CONTINUED PROTECTION AGAINST THE RISK OF ELECTRIC SHOCK, CUSTOMER'S POWER SUPPLY MUST BE PROPERLY GROUNDED.

NOTE: GROUNDING SCREW TO HAVE A GREEN COLORED SLOTTED AND/OR HEX HEAD NO SUBSTITUTES. USE #1005

NOTE: THE SURFACE OF THE INSULATED WIRES MARKED (X) TO BE COLORED GREEN, WITH OR WITHOUT ONE OR MORE YELLOW STRIPES.

WIRING NOTE
 ALL WIRES #14 AWG, TYPE SEW/SF2 MINIMUM UNLESS OTHERWISE NOTED

LT3K
 240V 60HZ
 KILN SITTER
 W/LIM. TIMER
 & 4" TUBE
 ASSY KS7

CR6
 6-2/8-1 CORDSET
 6-50P CAP

POWER REQ'TS
 240 VOLTS
 1 PHASE
 60 HERTZ
 40 AMPS
 9600 WATTS

TO RE-ORDER ELEMENTS, SPECIFY		
DESCRIPTION	QTY	LOC
ELS233TB	2	TOP&BOT
ELS233M	2	MIDDLE

UL/CUL LISTED MAX. TEMP. 2350° F

COMMENTS	PARAGON INDUSTRIES 2011 SOUTH TOWN EAST BLVD MESQUITE, TEXAS 75149	PRODUCT DESCRIPTION 10 SIDES, 22.5"DIA, 22.25"DP 240V, 1PH, 60HZ, 40A, 9600W	PART NO.	REV
			S233	-
			WIRING DIAGRAM	