



**CAUTION**

TO PROVIDE CONTINUED PROTECTION AGAINST THE RISK OF ELECTRIC SHOCK, CUSTOMER'S POWER SUPPLY MUST BE PROPERLY GROUNDED.

NOTE: GROUNDING SCREW TO HAVE A GREEN COLORED SLOTTED AND/OR HEX HEAD NO SUBSTITUTES. USE #1005

NOTE: THE SURFACE OF THE INSULATED WIRES MARKED (X) TO BE COLORED GREEN, WITH OR WITHOUT ONE OR MORE YELLOW STRIPES.

**WIRING NOTE**

ALL WIRES #14 AWG, TYPE SEW/SF2 MINIMUM UNLESS OTHERWISE NOTED

LT3K  
240V 60HZ  
KILN SITTER  
W/LIM. TIMER  
& 4" TUBE  
ASSY KS7

**POWER REQ'TS**

240 VOLTS  
1 PHASE  
60 HERTZ  
45 AMPS  
10800 WATTS

CR6  
6-2/8-1 CORDSET  
6-50P CAP

TO RE-ORDER ELEMENTS, SPECIFY		
DESCRIPTION	QTY	LOC
ELS243TBM	6	TOP, BOT & MID

UL/CUL LISTED

MAX TEMP 2350° F

COMMENTS	PARAGON INDUSTRIES 2011 SOUTH TOWN EAST BLVD MESQUITE, TEXAS 75149	<u>PRODUCT DESCRIPTION</u> 10 SIDES, 22.5"DIA, 29"DP 240V, 1PH, 60HZ, 45A, 10800W		<u>PART NO.</u> S243	<u>REV</u> -
		WIRING DIAGRAM			