



NOTE: SURFACE OF INSULATED WIRES ONLY MARKED ⊗ TO BE COLORED GREEN WITH OR WITHOUT ONE OR MORE YELLOW STRIPES.
 NOTE: GROUNDING SCREW TO HAVE A GREEN COLORED SLOTTED AND/OR HEXAGONAL HEAD, NO SUBSTITUTES. USE PPN-1250

CAUTION!
 TO PROVIDE CONTINUED PROTECTION AGAINST THE RISK OF ELECTRIC SHOCK CUSTOMER'S POWER SUPPLY MUST BE PROPERLY GROUNDED

WIRING NOTE
 ALL WIRES #14 AWG, TYPE SEW/SF2 MINIMUM UNLESS OTHERWISE NOTED

POWER REQ'TS
 240 VOLTS
 1 PHASE
 60 HERTZ
 45 AMPS
 10800 WATTS
 MAX TEMP 2300°F

TO RE-ORDER ELEMENTS, SPECIFY		
DESCRIPTION	QTY	LDC
ELS99TBM	6	TOP, BOT & MID

COMMENTS	PARAGON INDUSTRIES 2011 SOUTH TOWN EAST BLVD MESQUITE, TEXAS 75149	PRODUCT DESCRIPTION	PART NO.	REV
		10 SIDES, 23.5" DIA X 27" DP 240V, 1PH, 60HZ, 45A, 10800W	S99	-
			WIRING DIAGRAM	